

- TOP HATCH WITH ELECTRICAL INTERLOCK
- 2. CONSTRUCTION: FORMED AND WELDED SHEET STEEL.
- 3. SURFACE PREPARATION: ABRASIVE CLEANED OR CHEMICALLY CLEANED AND PHOSPHATIZED

FINISH COLOR: PRIMER:

ASA 49 GRAY
TILE CLAD WB EPOXY
(24702501), PAR PART A, B73A200, GRAY PRIMER

PAINT: CENTURIAN POLYURETHANE

PART B, B73V200, CATALYST (24702502),

(24708500), B65W711,

ASA 49 GRAY B65V700, CATALYST

(24722500), 4. APPROXIMATE WEIGHT 2000 LBS

FIXED CASTER	15315100	FAULTLESS HX3438-6x3 OR EQUAL APPROVED BY ENGINEERING
SWIVEL CASTER	15321100	FAULTLESS HX1438-6x3 OR EQUAL APPROVED BY ENGINEERING

THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED. DESIGN SUBJECT TO CHANGE WITHOUT NOTICE. ©2010 SIMPLEX, INC. ALL RIGHTS RESERVED.

SIPPLEX' SPRINGFIELD, ILLINO						
SCALE :	APPROVED BY :		DRAWN BY : RER			
DATE: 08-02-10			REVISED :			
ATLAS-MEGAWATT WEATHER RESISTANT LOAD BANK PICTORIAL						
STANDARD			PRAWING NUMBER 211931			