

CONNECTION SIDE INTAKE SIDE CONTROL SIDE -129,250 4.000 I---|-4.000 **-**0.562 NOTES: ADD HOLE PATTERN AS REQUIRED 1. CONSTRUCTION: ALL WELDED FORMED STEEL FRAME, DOORS, PANELS AND SKID. 1/2" THICK FLANGE
OF 5" STRUCTURAL ANGLE. SKID AND STRUCTURAL MEMBERS 7GA HRS, DUTER SHELL 12GA HRS AND HINGED DOORS 14GA HRS. 95.124 ALL HINGES, EXTERIOR FASTENERS, AND EXTERIOR HARDWARE ARE STAINLESS STEEL ABRASIVE CLEANED OR CHEMICALLY CLEANED AND PHOSPHATIZED ASA 49 GRAY 2. SURFACE PREPARATION: FINISH COLOR: TILE CLAD WB EPOXY (24702501), PART A, B73A200, PRIMER: (24702502), PART B, B73V200, CENTURION POLYURETHANE PAINT: B65W711, ASA 49 GRAY (24708500), (24722500), B65V700, 3. APPROXIMATE SHIPPING WEIGHT: 17,000 TO 25,000 LBS. TOTAL UNIT 4. LATCHES- CUP LATCH WITH KEY LOCK

THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED. DESIGN SUBJECT TO CHANGE WITHOUT NOTICE.
©2010 SIMPLEX, INC. ALL RIGHTS RESERVED.

<u>FOOTPRINT</u>

SPRINGFIELD, ILLINOIS

SCALE:
DATE: 08-02-10

LOADCUBE LOAD BANK PICTORIAL

STANDARD

SPRINGFIELD, ILLINOIS

DRAWN BY: RER

REVISED:

DRAWING NUMBER

211935