



NOTES:

1. BOTTOM OF CONTROL COMPARTMENT AVAILABLE FOR CONDUIT ENTRY.
2. CONSTRUCTION: ALL WELDED FORMED STEEL FRAME, DOORS, PANELS AND SKID. FORK LIFT TUBES 7GA HRS, OUTER SHELL 12GA HRS, BASE SKID, CONTROL BOX AND DOORS 14GA HRS, FAN/ELEMENT DOORS 16GA HRS ALL HINGES, EXTERIOR FASTENERS, AND EXTERIOR HARDWARE ARE STAINLESS STEEL. EXHAUST HOOD IS GALVANIZED SHEET STEEL, RIVETED
3. SURFACE PREPARATION: ABRASIVE CLEANED OR CHEMICALLY CLEANED AND PHOSPHATIZED
 FINISH COLOR: ASA 49 GRAY
 PRIMER: RECOATABLE EPOXY PRIMER
 (24702600), PART G, B67H5, BUFF PRIMER
 (24702700), PART H, B67V5, CATALYST
 PAINT: POLANE HS PLUS POLYURETHANE
 (24702800), F63JXA5108-1407, ASA 49 GRAY
 (24702801), V66V55, CATALYST
 (24702802), V66VB11, ACCELERATOR
4. APPROXIMATE SHIPPING WEIGHT: 1,590 LBS TOTAL UNIT
 : 1,300 LBS TOTAL UNIT
 : 290 LBS TOP HAT

THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED. DESIGN SUBJECT TO CHANGE WITHOUT NOTICE.
 ©2010 SIMPLEX, INC. ALL RIGHTS RESERVED.

| | | |
|---------------------------------|--------------------------|-----------------------|
| SIMPLEX | | SPRINGFIELD, ILLINOIS |
| SCALE : | APPROVED BY : | DRAWN BY : RER |
| DATE : 08-02-10 | | REVISED : |
| NEPTUNE-650 LOAD BANK PICTORIAL | | |
| STANDARD | DRAWING NUMBER 211943 | |